

§ 35.03–15

46 CFR Ch. I (10–1–99 Edition)

§ 35.03–15 Shipboard stowage—TB/ALL.

(a) The approved buoyant work vests shall be stowed separately from the regular stowage of approved life preservers.

(b) The locations for the stowage of work vests shall be such as not to be easily confused with that for approved life preservers.

§ 35.03–20 Shipboard inspections—TB/ALL.

(a) Each work vest shall be subject to examination by a marine inspector to determine its serviceability. If found to be satisfactory, it may be continued in service, but shall not be stamped by a marine inspector with a Coast Guard stamp. If a work vest is found not to be in a serviceable condition, then such work vest shall be removed from the vessel. If a work vest is beyond repair, it shall be destroyed or mutilated in the presence of a marine inspector so as to prevent its continued use as a work vest.

§ 35.03–25 Additional requirements for hybrid work vests.

(a) In addition to the other requirements in this subpart, commercial hybrid PFD's must be—

(1) Used, stowed, and maintained in accordance with the procedures set out in the manual required for these devices by § 160.077–29 of this chapter and any limitation(s) marked on them; and

(2) Of the same or similar design and have the same method of operation as each other hybrid PFD carried on board.

[CGD 78–174A, 51 FR 4350, Feb. 4, 1986; 51 FR 15497, Apr. 24, 1986]

Subpart 35.05—Officers and Crews

§ 35.05–1 Licensed officers and crews of tankships—T/ALL.

No tankship of the United States shall be navigated unless she shall have in her service and on board such complement of licensed officers and crew, including certificated lifeboatmen and certificated tankermen where required by the regulations in this subchapter,

separately stated, as called for in her certificate of inspection.

§ 35.05–5 [Reserved]

§ 35.05–10 [Reserved]

§ 35.05–15 Tank vessel security—TB/ALL.

(a) *Manned tank vessel.* At least one member of the crew of a manned tank vessel shall be on board at all times except when the vessel is gas free or is moored at a dock or terminal at which watchman service is provided.

(b) *Unmanned barge.* (1) The owner, managing operator, master, and person in charge of a vessel towing a tank barge that need not be manned, and each of them, shall be responsible for monitoring the security and integrity of the tank barge and for ensuring adherence to proper safety precautions. These responsibilities include, but are not limited to—

(i) Ensuring that any tank barge added to the tow has all tank openings properly secured; has its freeing-ports and scuppers, if any, unobstructed; meets any loadline or freeboard requirements; and neither leaks cargo into the water, voids, or cofferdams nor leaks water into the tanks, voids, or cofferdams;

(ii) Ensuring that every tank barge in the tow is properly secured within the tow;

(iii) Ensuring that periodic checks are made of every tank barge in the tow for leakage of cargo into the water, voids, or cofferdams and for leakage of water into the tanks, voids, or cofferdams;

(iv) Knowing the cargo of every tank barge in the tow, any hazards associated with the cargo, and what to do on discovery of a leak;

(v) Ensuring that the crew of the vessel know the cargo of every tank barge in the tow, any hazards associated with the cargo, and what to do on discovery of a leak;

(vi) Reporting to the Coast Guard any leaks from a tank barge in the tow into the water, as required by 33 CFR 151.15; and

(vii) Ensuring that the crew of the vessel and other personnel in the vicinity of the tank barges in the tow follow the proper safety precautions for tank